

# SystemC AMS extension — alignment with SystemC-TLM

Contribution to AMS-TLM Workshop January 2008


Martin Barnasconi



#### Requirements


- Interface and communication: SystemC TLM 2.0 compliant
  - using PVInitiator port and PVTarget port
  - support interrupt based synchronization (using sc core::sc out port)
- Register interface based on the (CoWare) SCML memory model
  - register interface splits communication in architecture context from functional modeling
  - note: internal register communication/callbacks not part of TLM standard
- Compatibility and Interoperability with digital functional models and subsystems
- Approach: Wrap SystemC AMS subsystem into 'TLM shell'
  - embed functional model in architecture block
  - two options
    - option 1: Plain SystemC FIFO interface
    - option 2: communicate directly to SystemC AMS extension / TDF solver






anno 2006






anno 2007/8































#### **Conclusions**

- Compatibility and interoperability
  - using communication, protocol and payload as proposed by TLM WG
  - using SCML register interface similar to other sub-systems
- Embedding/wrapping of functional models
  - valid for AMS and digital subsystems
  - two approaches possible
    - 1. Based on standard SystemC FIFO and communication
    - 2. New register communication in SystemC AMS extensions (e.g. "TDF queues")
- Evaluation of pros and cons for both options
  - Impact on standardization for both AMS and TLM
  - future AMS/TLM (in)dependency
  - Impact on simulation performance, flexibility, compatibility and interoperability



